

DSP915

Public Address System-Ceiling Speaker



Specifications

The DSP915 is a ceiling speaker; it can be switched between the voltage terminal and the ohms terminal. The 70v/100v transmission is realized in a high-voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple loudspeakers possible. The built-in 5" speaker driver is designed of wide frequency response (60-20,000Hz), and rated power output is 20W; It is made of high quality engineering plastic, which ensures long-term durability, and will never be out of shape; Construction of dual-crossover, its flush mount type makes the easy and secure installation possible; Driver surround excellent damping, long life, clear and sonorous sounds. It is an ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

Description

- Built-in 100v/70v transformer
- In-ceiling type loudspeaker
- Rated power output at 20W
- High sensitivity(90±2dB) with voltage and ohms terminal
- ABS white engineering plastic
- Secure flush mount installation

Features

Model	DSP915
Full-range	5" x 1, 1" x1"
Rated Power	20W
Line Input	70/100V, 4-16Ω
Sensitivity (1M,1W)	90dB±2dB
Max SPL(1M)	103dB±2dB
Freq. Response	60Hz-20kHz
Cutout Size	Ø170 mm
Dimensions (H x W x L)	224 x Ø198mm
Weight	2.9kg