

## DMX08 DMX12 DMX16

### Professional Mixing Console



**DMX08**



**DMX12**



**DMX16**

### *Features*

- With 8/12/16 XLR balanced mono channel inputs, ultra-low noise circuit design, and large dynamic headroom.
- Each channel has 3-band EQ adjustment, MUTE switch, and 60MM fader attenuator.
- With 1 stereo bus output + 2 AUX bus outputs (including FX).
- With 1 return, and 1 RAC output.
- With built-in 48V phantom power supply.
- With built-in 16 kinds of DSP digital effects.
- Support USB audio playback and USB recording.
- With built-in Bluetooth to receive and play MP3.
- Support LED display of the playback status.
- With 10-band three-color level indicator display.
- Applicable to global power supply voltage of 30W; flexible to use, featuring no noise, good instant response and low power consumption.

## Specifications

Items	DMX08	DMX12	DMX16
MAX. Output Level	18dB		
S/N	≥83dB		
THD	≤0.02% @0dB 1KHz		
Frequency Response	20Hz~20KHz±0.5dB		
Channel Crosstalk	<-75dB @ 1KHz		
Input Impedance MIC	600Ω		
LINE	10KΩ		
Output Impedance	100Ω		
MIC IN	-60dB		
LINE IN	-40dB		
Stereo Input Impedance	10KΩ	/	
Channel Gain	-30dB	/	
3-band EQ	±15dB	/	
HI	12KHz 15dB ±3dB	/	
MID	2.5KHz 15dB ±3dB	/	
LOW	80Hz 15dB ±3dB	/	
Output Power	30W	/	
Power Supply	100V-240V/50Hz	/	
Package Dimensions	440×440×165mm	555×440×165mm	670×440×165mm
Product Dimensions	385×367×100mm	505×367×100mm	620×367×100mm
Gross Weight	5kg	6kg	7.5kg
Net Weight	4kg	5kg	6.2kg